

COMPANY or Name	Delivery Adress (if different to invoice)	ORDER	QUOTE	Page	of
Email :		Order Date: / /			
Invoice Address :		Req'd Date: / /			
		Signed:			
		ENERGY RATING	A		
Telephone :	Site contact :	PAS24 / SBD Enhanced Security	YES	NO	
CUSTOMER REF:	Additional information / Instructions				
Project Type					
Extension <input type="checkbox"/> Conservation area <input type="checkbox"/> Replacement <input type="checkbox"/> Grade listed status <input type="checkbox"/> Newbuild <input type="checkbox"/>					

VS WINDOW SPECIFICATION

Window Colour:	Standard Colours >>>	White PVC	White FOIL	Cream FOIL	Anthracite GREY On White	Cream FOIL On White	Fastrack Colours >>>	Agate Grey On White	Chartwell Green On White	Special Foil or RAL Spray colour	OUTSIDE
Hardware Colour:	WHITE	GOLD	CHROME	FLAT BLACK	SATIN SILVER	GRAPHITE	BRONZE	ANTIQUÉ BLACK		Special Foil or RAL Spray colour	INSIDE
Spacer Bar Colour:	BLACK WARMEDGE	WHITE WARMEDGE	GREY WARMEDGE								

VERTICAL SLIDING SASH SPEC/INFO

Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Weather Bar (Fitted across cill where it meets lower sash)	YES	NO	
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES	NO	

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please indicate clearly any Add-on and Georgian bar detail

Width Available add ons | 15mm | 30mm

Height

Split

Top Glass Type	Bottom Glass Type	Georgian Bar	
Toughened	Obscure	Toughened	Obscure
		Internal (18mm)	Astragal (22mm)

VERTICAL SLIDING SASH SPEC/INFO

Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Weather Bar (Fitted across cill where it meets lower sash)	YES	NO	
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES	NO	

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please indicate clearly any Add-on and Georgian bar detail

Width

Height

Split

Top Glass Type	Bottom Glass Type	Georgian Bar	
Toughened	Obscure	Toughened	Obscure
		Internal (18mm)	Astragal (22mm)

VERTICAL SLIDING SASH SPEC/INFO			
Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)		DEEP RAIL (milled)
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES		NO
Weather Bar (Fitted across cill where it meets lower sash)	YES		NO
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES		NO

SIZES TO INCLUDE ALL CILLS AND ADD-ON					
Please indicate clearly any Add-on and Georgian bar detail					
Width		Available add ons 15mm 30mm			
Height					
Split					
Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)

VERTICAL SLIDING SASH SPEC/INFO			
Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)		DEEP RAIL (milled)
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES		NO
Weather Bar (Fitted across cill where it meets lower sash)	YES		NO
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES		NO

SIZES TO INCLUDE ALL CILLS AND ADD-ON					
Please indicate clearly any Add-on and Georgian bar detail					
Width		Available add ons 15mm 30mm			
Height					
Split					
Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)

VERTICAL SLIDING SASH SPEC/INFO			
Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)		DEEP RAIL (milled)
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES		NO
Weather Bar (Fitted across cill where it meets lower sash)	YES		NO
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES		NO

SIZES TO INCLUDE ALL CILLS AND ADD-ON					
Please indicate clearly any Add-on and Georgian bar detail					
Width		Available add ons 15mm 30mm			
Height					
Split					
Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)

VERTICAL SLIDING SASH SPEC/INFO			
Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)		DEEP RAIL (milled)
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES		NO
Weather Bar (Fitted across cill where it meets lower sash)	YES		NO
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES		NO

SIZES TO INCLUDE ALL CILLS AND ADD-ON					
Please indicate clearly any Add-on and Georgian bar detail					
Width		Available add ons 15mm 30mm			
Height					
Split					
Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)

COMPANY or Name	Delivery Address (if different to invoice)	ORDER	QUOTE	Page	of
Email :		Order Date: / /			
Invoice Address :		Req'd Date: / /			
		Signed:			
		ENERGY RATING	A		
Telephone :	Site contact :	PAS24 / SBD Enhanced Security	YES	NO	
CUSTOMER REF:	Additional information / Instructions				
Project Type					
Extension <input type="checkbox"/> Replacement <input type="checkbox"/> Newbuild <input type="checkbox"/>	Conservation area <input type="checkbox"/> Grade listed status <input type="checkbox"/>				

VS BAY & WELDED CILL DETAIL SHEET

Window Colour:	Standard Colours >>>	White PVC	White FOIL	Cream FOIL	Anthracite GREY On White	Cream FOIL On White	Fastrack Colours >>>	Agate Grey On White	Chartwell Green On White	Special Foil or RAL Spray colour	OUTSIDE
Hardware Colour:	WHITE	GOLD	CHROME	FLAT BLACK	SATIN SILVER	GRAPHITE	BRONZE	ANTIQUÉ BLACK		Special Foil or RAL Spray colour	INSIDE
Spacer Bar Colour:	BLACK WARMEDGE	WHITE WARMEDGE	GREY WARMEDGE								

VERTICAL SLIDING SASH SPEC/INFO

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Weather Bar (Fitted across cill where it meets lower sash)	YES	NO	
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES	NO	

Please indicate clearly any Add-on and Georgian bar detail

	A Left Side	B Front	C Right Side
Split			

Available add ons | 15mm | 30mm

Top Glass Type		Bottom Glass Type		Georgian Bar	
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astragal (22mm)

INTERNAL CILL SIZES, OVERALL HEIGHTS & ANGLES

DRAW CILL PLAN BELOW

Left side 'A' internal cill size
Front 'B' internal cill size
Right side 'C' internal cill size
Overall Height
Left Angle (Variable angle VS bay post 120 to 150 degrees only)
Right Angle (Variable angle VS bay post 120 to 150 degrees only)

90 DEGREE FIXED ANGLE VS BAY POST ALSO AVAILABLE

IF YOU DO NOT REQUIRE A WELDED CILL & BAY POSTS USE THE SINGLE VS OR MULTI-SEGMENT FORMS WHEN ORDERING

ALL BAYS ARE PRE ASSEMBLED AND READY TO FIT. THE CILL WILL BE 300mm LONGER AT EACH SIDE

COMPANY or Name	Delivery Adress (if different to invoice)	ORDER	QUOTE	Page	of
Email :		Order Date: / /			
Invoice Address :		Req'd Date: / /			
		Signed:			
		ENERGY RATING	A		
Telephone :	Site contact :	PAS24 / SBD Enhanced Security	YES	NO	
CUSTOMER REF:	Additional information / Instructions				
Project Type					
Extension <input type="checkbox"/> Replacement <input type="checkbox"/> Conservation area <input type="checkbox"/> Newbuild <input type="checkbox"/> Grade listed status <input type="checkbox"/>					

VS MULTI SEGMENT DETAIL SHEET

Window Colour:	Standard Colours >>>	White PVC	White FOIL	Cream FOIL	Anthracite GREY On White	Cream FOIL On White	Fastrack Colours >>>	Agate Grey On White	Chartwell Green On White	Special Foil or RAL Spray colour	OUTSIDE	
Hardware Colour:	WHITE	GOLD	CHROME	FLAT BLACK	SATIN SILVER	GRAPHITE	BRONZE	ANTIQUE BLACK	Special Foil or RAL Spray colour			INSIDE
Spacer Bar Colour:	BLACK WARMEDGE	WHITE WARMEDGE	GREY WARMEDGE									

VERTICAL SLIDING SASH SPEC/INFO			
Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Weather Bar (Fitted across cill where it meets lower sash)	YES	NO	
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES	NO	

SIZES TO INCLUDE ALL CILLS AND ADD-ON			
Please indicate clearly any Add-on and Georgian bar detail			
	Width		
↑		↓	Height
Split			
Available add ons 15mm 30mm			
Top Glass Type	Bottom Glass Type	Georgian Bar	
Toughened	Obscure	Toughened	Obscure
		Internal (18mm)	Astragal (22mm)

VERTICAL SLIDING SASH SPEC/INFO			
Location:	Quantity:		
Sash Horns (No horns unless stated)	Run Through (Milled)	None	Mock / Plant on (Welded VS Only)
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm – 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Restrictor Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Weather Bar (Fitted across cill where it meets lower sash)	YES	NO	
Slim Meeting Rail (37mm) Only on fully mechanical window & sash horns	YES	NO	

SIZES TO INCLUDE ALL CILLS AND ADD-ON			
Please indicate clearly any Add-on and Georgian bar detail			
	Width		
↑		↓	Height
Split			
Available add ons 15mm 30mm			
Top Glass Type	Bottom Glass Type	Georgian Bar	
Toughened	Obscure	Toughened	Obscure
		Internal (18mm)	Astragal (22mm)